



LUBEGARD® for **V-TWIN'S**
Transmission Protectant

BENEFITS

- Suitable for use in all 4 and 5 speed FL, FLT, FX, FXD and FXR Transmissions or any separate sump transmission applications.
- Exclusive LXE® Technology for enhanced heat reduction and extended transmission fluid life.
- Improves shift quality.
- Reduces drive train power loss.
- Reduces wear on gears and bearings.
- Increases heat transfer from inside case through unit case wall.

#40602

DIRECTIONS:

Add contents of bottle directly to transmission. (4 oz. per Quart of Transmission Fluid)



LUBEGARD® for **V-TWIN'S**
Engine Oil Protectant

BENEFITS

- Suitable for use in all '84 and later FL, FLT, FX, FXD, FXR, and FXST engines or any 4 cycle V-Twin engine application with separate oil sump.
- For use with conventional or synthetic motorcycle engine oil.
- Exclusive LXE® Technology for enhanced heat reduction and extended life for the engine.
- Increases heat transfer from inside engine case through engine case wall for reduced engine temperatures.
- Reduces wear on all metal surfaces. Eliminates wear from cold start up.
- Better fuel mileage with extended oil life.
- Contains no harmful additives such as chlorinated hydrocarbons or solid lubricants like Teflon or graphite.

#40910

DIRECTIONS:

Add contents of bottle directly to engine. Bottle will treat 3-4 Quart capacity sump. (3 oz. per Quart of engine oil)



LUBEGARD® Primary Case Chain Protectant for **V-TWIN'S**

BENEFITS

- Suitable for use in '84 and later FL, FLT, FX, FXD, FXR and FXST Models with Wet Type diaphragm Spring Clutch.
- For use with conventional or synthetic motorcycle primary chain case fluid.
- Exclusive LXE® Technology for enhanced heat reduction, reduced wear and extended life for the primary chain.
- Formulated to prevent clutch chatter, shudder and slippage while maintaining the proper coefficient of friction for long life and proper clutch operation.
- Improves shift quality.
- Increases heat transfer from inside primary case through primary unit case wall.

#40104

DIRECTIONS:

Add contents of bottle directly to primary case. (4 oz. per Quart of Primary Fluid)



LUBEGARD® Coolant Treatment for Water-Cooled Motorcycles & ATVs

BENEFITS

- Protects aluminum from electrolysis
- Reduces operating temperatures
- Provides 5 year corrosion protection
- Prevents hard-water scales and deposits

DIRECTIONS:

Directions: With engine cool, pour into radiator, start engine and run 10 min. Always maintain a minimum of 15% antifreeze in street-driven motorcycles. Ratio: 1 bottle treats systems 2-6 qrts in capacity. Frequency: Add 1 bottle every year or 30,000 miles. After 5th consecutive year, drain, flush, and refill cooling system.

#40820

AVAILABILITY:

Stock No.	Unit Size	Case Weight/QNTY
40602	4 oz.	3.75 lbs. (12/c)
40910	10 oz.	8.78 lbs. (12/c)
40104	4 oz.	3.75 lbs. (12/c)
40820	4 oz.	3.75 lbs. (12/c)

